CONFIGURATIONS







2





- FEATURES


Resistance to:



Shocks







— HOMOLOGATION—



E57) 73 R - 010014

Homologation as Lateral Protection System.

- CERTIFICATION -



UNI EN ISO 3834-3 certified welding process.

- PRODUCT TESTS

TÜV RHEINLAND





Dust and water resistance Durability test

Vibrations test led with Daken brackets both on the horizontal and on the vertical axis.

MODELS

CODE	L	Dimensions (mm) H	D	Weight (kg)	Handles N°	Capacity (lt)
8 Z 74 00	400	300	300	4,2	1	32
8 Z 7410	500	350	400	6,1	1	63
8 Z 7420	600	400	500	8,6	1	108
8 Z 7440	800	500	500	12,2	2	180
8 Z 7460	1000	500	500	14,5	2	225
8 Z 7480	1200	500	500	16,9	2	270





Aluminium toolbox with NexT handle Lightweight toolbox

entirely made of aluminium and extremely resistant to atmospheric corrosion.

Finishing: aluminium.
Lid configurations:

1: aluminium

2: anodised aluminium Thickness: 2,0 mm

Closing system: NexT handle in nylon.

Hinges material: nylon.

roduction process: laser cut, bending, TIG welding.

_ OPTIONALS

Customised dimensions	Aluminium hinges	Opening position	Pistons / Chain / Steel cable	Label with customised logo	Shelves and dividers kit
	©	②	÷00:	10 10	
Drawer	Drawer Internal mat		Lights kit	Full metal upgrade	Customised brackets
	00.*	*Minimum order quantity			,





*Minimum order quantity to be agreed.